

WHAT IS CLAIMED IS:

Sub  
A1

1. A method for copying data in a memory device system having a plurality of memory devices as partitioned into a group of n memory devices and a group of m memory devices, said method including the steps of:

reading from said n memory devices data with a length required for preparation of redundant data;  
forming redundant data from the read data;  
and

storing said read data and said redundant data in said m memory devices.

2. The method according to claim 1 wherein at said step of storing, only part of said read data is stored in said m memory devices.

3. A method for copying data in a memory device system being connected to external apparatus and having a plurality of memory devices as partitioned into n memory devices and m memory devices, said method including the steps of:

duplexing and storing data as sent from said external apparatus in said n memory devices and said m memory devices;

halting duplex of data based on an instruction from said external apparatus;

storing the data as sent from said external apparatus during interruption of data duplex in said n memory devices while recording information as to a

10087524-00000000



6. The system according to claim 4 further including:

an interface connected to external apparatus;  
duplex means for duplexing and storing data  
in said n memory devices and said m memory devices;

means for interrupting said duplex means in  
accordance with an instruction from said external  
apparatus; and

update management means for recording  
information as to a location whereat data being input  
from said interface is to be stored in said n memory  
devices during interruption of said duplex means,

wherein said m control means stores any one  
of said m-1 unit read data in any one of said m memory  
devices on the basis of information as stored in said  
update management means.

7. A memory device system including:

a plurality of memory devices as partitioned  
into n memory devices and m memory devices;

a controller for control of said plurality of  
memory devices;

n control means for controlling said n memory  
devices;

m control means for controlling said m memory  
devices; and

data duplex means for duplexing and storing  
data in said n memory devices and said m memory  
devices.

10067524.00000000

8. The system according to claim 7 wherein n and m are different integers.

9. A computer system comprising a first memory device system with n memory devices; and  
a second memory device system being connected to said first memory device system and having m memory devices,

wherein said first memory device system includes means for reading data of m-1 unit out of said n memory devices; and

said second memory device system includes formation means for forming redundant data based on the m-1 unit data as read by said first memory device system, and means for storing said redundant data as formed by said formation means and said m-1 unit read data in said m memory devices.

10. A computer system comprising:

a computer; and

a memory device system having a plurality of storage media, wherein

said memory device system includes:

a mirror primary LU;

a mirror secondary LU;

an n-RAID control subprogram for performing RAID control of the mirror primary LU;

an m-RAID control subprogram for performing RAID control of the mirror secondary LU;

an LU mirror subprogram for writing for

10067524.00000000

a non-mirror event update monitor subprogram for monitoring data update with respect to said mirror primary LU upon interruption of duplexing of said mirror primary LU and said mirror secondary LU;

a mirror resynchronous subprogram for copying data of the recorded update position from said mirror primary LU to said mirror secondary LU to thereby establish content coincidence, and said mirror primary LU and said mirror secondary LU are different from each other in arrangement of redundant array of inexpensive disks ("RAID").

11. The computer system according to claim 10 wherein said mirror primary LU is formed of  $nD+1P$  whereas said mirror secondary LU is made up of  $mD+1P$ , and wherein  $m$  and  $n$  are integers more than or equal to two and are of different values.

12. The computer system according to claim 10 wherein said mirror resynchronous subprogram executes processing for establishing content coincidence by copying the data of said recorded update position from said mirror primary LU to said mirror secondary LU and wherein said m-RAID control subprogram performs

processing of reading data out of said mirror primary LU to thereby permit assortment of data of a stripe array of said mirror secondary LU including the data of said recorded updated position.

13. A computer system comprising:

a computer; and

a first memory device system and a second memory device system each having a plurality of storage media, wherein

said first memory device system includes:

a mirror primary LU;

an n-RAID control subprogram for performing RAID control of said mirror primary LU;

an LU mirror subprogram for writing for duplex purposes said data into said mirror primary LU and a mirror secondary LU when said computer issues a data write request;

a non-mirror update monitor subprogram for monitoring data update with respect to said mirror primary LU during interruption of duplex of said mirror primary LU and said mirror secondary LU;

a non-mirror event update position management subprogram for recording an update position of said data update with respect to said mirror primary LU;

a mirror resynchronous subprogram for copying data of said recorded update position from said mirror primary LU to said mirror secondary LU to thereby permit establishment of content coincidence; and

10067564-022602

a command issuance subprogram for issuing a command for execution of data transfer relative to the second external memory device; and

said second memory device system includes:

a mirror secondary LU; and

an m-RAID control subprogram for performing RAID control of said mirror secondary LU, and said mirror primary LU and said mirror secondary LU are different in RAID level from each other.

14. The computer system according to claim 13 wherein said mirror primary LU is formed of  $nD+1P$  whereas said mirror secondary LU is made up of  $mD+1P$ , and wherein  $m$  and  $n$  are integers of more than or equal to two and are different in value from each other.

a

10067524.000000